

# Reval 182

The **Reval 182** is one of the **pilot-operated gas pressure regulators** designed and manufactured by Pietro Fiorentini. This device is suitable for use with previously filtered non-corrosive gases, and it is mainly used for medium and low pressure natural gas distribution networks. According to the European Standard EN 334, it is classified as **Fail Close**.



Gas engines

Medium / small  
industry

District stations

| Features  | Values   |
|---|--|
| Design pressure* (PS <sup>1</sup> / DP <sup>2</sup> )                     | up to 2.5 MPa<br>up to 25 barg   |
| Ambient temperature* (TS <sup>1</sup> )                                   | from -20 °C to +60 °C<br>from -4 °F to +140 °F   |
| Inlet gas temperature*  | from -20 °C to +60 °C<br>from -4 °F to +140 °F   |
| Inlet pressure (MAOP / p <sub>umax</sub> <sup>1</sup> )                   | from 0.02 to 2.5 MPa<br>from 0.2 to 25 barg  |
| Range of downstream pressure (Wd <sup>1</sup> )                           | from 0.7 KPa to 1.2 MPa<br>from 7 mbarg to 12 barg   |
| Available accessories   | DB/182 Silencer, PM/182 Monitor, SB/82 Slam shut, SA Slam shut HB/97 Slam shut, opening indicator          |
| Minimum operating differential pressure (Δp <sub>min</sub> <sup>1</sup> ) | 0.01 MPa   0.1 barg  |
| Accuracy class (AC <sup>1</sup> )   | up to 2.5  |
| Lock-up pressure class (SG <sup>1</sup> )                                 | up to 5  |
| Nominal size (DN <sup>1,2</sup> )   | DN 25   1"; DN 50   2"; DN 65   2" 1/2; DN 80   3";<br>DN 100   4"; DN 150   6"; DN 200   8"; DN 250   10" |
| Connections   | Class 150 RF or RTJ according to ASME B16.5 and PN16, 25 and 40 according to ISO 7005                      |

(<sup>1</sup>) according to EN334 standard  
(<sup>2</sup>) according to ISO 23555-1 standard  
(\*) NOTE: Different functional features and/or extended temperature ranges may be available on request. Stated inlet gas temperature range is the maximum for which the equipment's full performance, including accuracy is guaranteed. Product may have a different pressure or temperature ranges according to the version and/or installed accessories.

**Table 1** Features

## Materials and Approvals

| Part                 | Material  |
|----------------------|---|
| Body                 | Cast steel ASTM A216 WCB for all sizes<br>Ductile iron GS 400-18 ISO 1083 for Size ≤ 8" |
| Heads                | Die stamped carbon steel  |
| Stem                 | AISI 416 Stainless steel  |
| Plug                 | ASTM A 350 LF2 Nickel coated on sealing surfaces  |
| Seat                 | Steel + vulcanized rubber   |
| Diaphragm            | Rubberized canvas   |
| O-rings              | Nitrile Rubber  |
| Compression fittings | In zinc-plated carbon steel according to DIN 2353<br>Stainless steel on request         |

**NOTE:** The materials indicated above refer to the standard models. Different materials can be provided according to specific needs.

**Table 2** Materials

The **Reval 182** regulator is designed according to the European standard EN 334. The regulator reacts in closing (Fail Close) according to EN 334. The product is certified according to European Directive 2014/68/EU (PED). Leakage class: bubble tight, better than VIII according to ANSI/FCI 70-3.



EN 334



PED-CE

## Reval 182 competitive advantages



Compact and simple design



Top Entry



High accuracy



Easy maintenance



High turn-down ratio



In-built accessories



Fail Close plug and seat regulator



Balanced type



Built-in pilot filter



Biomethane compatible and  
20% Hydrogen blending compatible.  
Higher blending available on request